

OCT 11 2007

- 2 -

Application No. 09/651,889
Docket No. 740756-2205**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently amended) A semiconductor device comprising:
a TFT formed over a substrate;
an active layer formed in the TFT; and
a first region, a second region and a third region formed in the active layer, the third region being formed between the first region and the second region,
wherein the third region includes a channel forming region,
wherein the third region has a first width and a second width.
wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region,
wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a direction perpendicular to a carrier flow direction, and
wherein a portion of the third region is convexed or concaved in the direction perpendicular to the carrier flow direction, which is parallel to a plane of the substrate.
2. (Currently amended) A semiconductor device comprising:
a TFT formed over a substrate;
an active layer formed in the TFT; and
a first region, a second region and a third region formed in the active layer, the third region being formed between the first region and the second region,
wherein the third region includes a channel forming region,
wherein the third region has a first width and a second width.
wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region,
wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a direction perpendicular to a carrier flow direction,

- 3 -

Application No. 09/651,889
Docket No. 740756-2205

wherein a portion of the third region is convexed or concaved in the direction perpendicular to the carrier flow direction, which is parallel to a plane of the substrate, and wherein zero or one grain boundary is contained in the channel forming region.

3. (Currently amended) A semiconductor device comprising:

a TFT formed over a substrate;

an active layer formed in the TFT; and

a first region, a second region and a third region formed in the active layer, the third region being formed between the first region and the second region,

wherein the third region includes a channel forming region,

wherein the third region has a first width and a second width.

wherein a width the first width and the second width of the third region [[is]] are narrower than a width of the first region and a width of the second region,

wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a direction perpendicular to a carrier flow direction,

wherein a portion of the third region is convexed or concaved in the direction perpendicular to the carrier flow direction, which is parallel to a plane of the substrate, and

wherein the number of grain boundaries crossing the channel forming region in a width direction of the channel forming region is zero or one.

4. (Withdrawn) A method of manufacturing a semiconductor device, comprising the steps of:

forming a semiconductor film over a substrate;

forming a crystalline semiconductor film by irradiating a laser light to said semiconductor film;

forming a convex portion or a concave portion in a region which is a portion of said crystalline semiconductor film and which later contains a channel forming region; and

irradiating the laser light to said crystalline semiconductor film in which the convex portion or the concave portion is formed.

- 4 -

Application No. 09/651,889
Docket No. 740756-2205

5. (Withdrawn) A method of manufacturing a semiconductor device, comprising the steps of:

forming a semiconductor film over a substrate;

forming a crystalline semiconductor film by irradiating a laser light to said semiconductor film;

forming a convex portion or a concave portion in a region which is a portion of said crystalline semiconductor film and which later contains a channel forming region; and

irradiating the laser light to the top surface and to the bottom surface of said crystalline semiconductor film in which the convex portion or the concave portion is formed.

6. (Withdrawn) A method of manufacturing a semiconductor device, comprising the steps of:

forming a semiconductor film over a substrate;

forming semiconductor islands by patterning said semiconductor film, each of said semiconductor island having a convex portion or a concave portion in a region which later contains a channel forming region, and

crystallizing said semiconductor islands by irradiating a laser light.

7. (Withdrawn) A method of manufacturing a semiconductor device, comprising the steps of:

forming a semiconductor film over a substrate;

forming semiconductor islands by patterning said semiconductor film, each of said semiconductor island having a convex portion or a concave portion in a region which later contains a channel forming region, and

crystallizing said semiconductor islands by irradiating a laser light to the top surface and to the bottom surface thereof.

8. (Withdrawn) The method of manufacturing a semiconductor device according to claim 5, wherein a relationship of $0 < (I_0' / I_0) < 1$, or a relationship of $1 < (I_0' / I_0)$, exists between the effective energy strength of the laser light irradiated on the top surface of said

- 5 -

Application No. 09/651,889
Docket No. 740756-2205

semiconductor film (I_0) and the effective energy strength of the laser light irradiated on the bottom surface of said semiconductor film (I_0').

9. (Withdrawn) The method of manufacturing a semiconductor device according to claim 7, wherein a relationship of $0 < (I_0' / I_0) < 1$, or a relationship of $1 < (I_0' / I_0)$, exists between the effective energy strength of the laser light irradiated on the top surface of said semiconductor island (I_0') and the effective energy strength of the laser light irradiated on the bottom surface of said semiconductor island (I_0).

10. (Previously Presented) A semiconductor device according to any one of claims 1 to 3, wherein said semiconductor device is incorporated into an electronic device selected from the group consisting of a personal computer, a projector, a digital camera, a video camera, a head mounted display, a portable information terminal, a navigation system, a game machine, an image playback machine and a music playback machine.

11. (Currently amended) A semiconductor device comprising:
a semiconductor layer formed over a substrate; and
a first region, a second region and a third region formed in the semiconductor layer, the third region being formed between the first region and the second region,
wherein the third region includes a channel forming region,
wherein the third region has a first width and a second width.
wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region,
wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a direction perpendicular to a channel length direction, and
wherein a portion of the third region is convexed in the direction perpendicular to the channel length direction and parallel to a plane of the substrate.

12. (Currently amended) A semiconductor device comprising:
a semiconductor layer formed over a substrate; and

- 6 -

Application No. 09/651,889
Docket No. 740756-2205

a first region, a second region and a third region formed in the semiconductor layer, the third region being formed between the first region and the second region, wherein the third region includes a channel forming region, wherein the third region has a first width and a second width. wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region, wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a direction perpendicular to a channel length direction, and wherein a portion of the third region is concaved in the direction perpendicular to the channel length direction and parallel to a plane of the substrate.

13. (Currently amended) A semiconductor device comprising:
a semiconductor layer formed over a substrate; and
a first region, a second region and a third region formed in the semiconductor layer, the third region being formed between the first region and the second region, wherein the third region includes a channel forming region, wherein the third region has a first width and a second width. wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region, wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a channel width direction, and wherein a portion of the third region is convexed in the channel width direction, the channel width direction being parallel to a plane of the substrate.

14. (Currently amended) A semiconductor device comprising:
a semiconductor layer formed over a substrate; and
a first region, a second region and a third region formed in the semiconductor layer, the third region being formed between the first region and the second region, wherein the third region includes a channel forming region,

- 7 -

Application No. 09/651,889
Docket No. 740756-2205

wherein the third region has a first width and a second width.

wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region,

wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a channel width direction, and

wherein a portion of the third region is concaved in the channel width direction, the channel width direction being parallel to a plane of the substrate.

15. (Currently amended) A semiconductor device comprising:

a semiconductor layer formed over a substrate; and

a first region, a second region and a third region formed in the semiconductor layer, the third region being formed between the first region and the second region,

wherein the third region includes a channel forming region,

wherein the third region has a first width and a second width.

wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region,

wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a direction perpendicular to a carrier flow direction, and

wherein a portion of the third region is convexed in the direction perpendicular to the carrier flow direction and parallel to a plane of the substrate.

16. (Currently amended) A semiconductor device comprising:

a semiconductor layer formed over a substrate; and

a first region, a second region and a third region formed in the semiconductor layer, the third region being formed between the first region and the second region,

wherein the third region includes a channel forming region,

wherein the third region has a first width and a second width.

wherein ~~a width~~ the first width and the second width of the third region ~~[[is]]~~ are narrower than a width of the first region and a width of the second region,

- 8 -

Application No. 09/651,889
Docket No. 740756-2205

wherein each of the first width and the second width of the third region, the width of the first region and the width of the second region is a length in a direction perpendicular to a carrier flow direction, and

wherein a portion of the third region is concaved in the direction perpendicular to the carrier flow direction and parallel to a plane of the substrate.

17. (Previously Presented) A semiconductor device according to any one of claims 11-16, wherein said semiconductor device is incorporated into an electronic device selected from the group consisting of a personal computer, a projector, a digital camera, a video camera, a head mounted display, a portable information terminal, a navigation system, a game machine, an image playback machine and a music playback machine.

18-20. (Canceled)

21. (Previously Presented) A semiconductor device according to claim 11, wherein the channel length direction is parallel to a direction in which a carrier flows from the first region to the second region.

22. (Previously Presented) A semiconductor device according to claim 12, wherein the channel length direction is parallel to a direction in which a carrier flows from the first region to the second region.

23. (Previously Presented) A semiconductor device according to claim 13, wherein the channel width direction is perpendicular to a direction in which a carrier flows from the first region to the second region.

24. (Previously Presented) A semiconductor device according to claim 14, wherein the channel width direction is perpendicular to a direction in which a carrier flows from the first region to the second region.

- 9 -

Application No. 09/651,889
Docket No. 740756-2205

25. (Previously Presented) A semiconductor device according to claim 11, wherein zero or one grain boundary is contained in the channel forming region.

26. (Previously Presented) A semiconductor device according to claim 12, wherein zero or one grain boundary is contained in the channel forming region.

27. (Previously Presented) A semiconductor device according to claim 13, wherein zero or one grain boundary is contained in the channel forming region.

28. (Previously Presented) A semiconductor device according to claim 14, wherein zero or one grain boundary is contained in the channel forming region.

29. (Previously Presented) A semiconductor device according to claim 15, wherein zero or one grain boundary is contained in the channel forming region.

30. (Previously Presented) A semiconductor device according to claim 16, wherein zero or one grain boundary is contained in the channel forming region.

31. (Previously Presented) A semiconductor device according to claim 11, wherein the number of grain boundaries crossing the channel forming region in a width direction of the channel forming region is zero or one.

32. (Previously Presented) A semiconductor device according to claim 12, wherein the number of grain boundaries crossing the channel forming region in a width direction of the channel forming region is zero or one.

33. (Previously Presented) A semiconductor device according to claim 13, wherein the number of grain boundaries crossing the channel forming region in the channel width direction is zero or one.

34. (Previously Presented) A semiconductor device according to claim 14, wherein the number of grain boundaries crossing the channel forming region in the channel width direction is zero or one.

- 10 -

Application No. 09/651,889
Docket No. 740756-2205

35. (Previously Presented) A semiconductor device according to claim 15, wherein the number of grain boundaries crossing the channel forming region in a width direction of the channel forming region is zero or one.

36. (Previously Presented) A semiconductor device according to claim 16, wherein the number of grain boundaries crossing the channel forming region in a width direction of the channel forming region is zero or one.

37. (Previously Presented) A semiconductor device according to claim 1, wherein the first region includes a source region and the second region includes a drain region.

38. (Previously Presented) A semiconductor device according to claim 2, wherein the first region includes a source region and the second region includes a drain region.

39. (Previously Presented) A semiconductor device according to claim 3, wherein the first region includes a source region and the second region includes a drain region.

40. (Previously Presented) A semiconductor device according to claim 11, wherein the first region includes a source region and the second region includes a drain region.

41. (Previously Presented) A semiconductor device according to claim 12, wherein the first region includes a source region and the second region includes a drain region.

42. (Previously Presented) A semiconductor device according to claim 13, wherein the first region includes a source region and the second region includes a drain region.

43. (Previously Presented) A semiconductor device according to claim 14, wherein the first region includes a source region and the second region includes a drain region.

44. (Previously Presented) A semiconductor device according to claim 15, wherein the first region includes a source region and the second region includes a drain region.

- 11 -

Application No. 09/651,889
Docket No. 740756-2205

45. (Previously Presented) A semiconductor device according to claim 16, wherein the first region includes a source region and the second region includes a drain region.